Gardner

COMPRESSOR DATA SHEET Denver Federal Uniform Test Method for Certain Air Compressors Not Applicable **Rotary Compressor: Variable Frequency Drive**

1	Manufacturer	: Ga	rdner D	enver								
	Model Numbe	er TV	'S55			Date:			ate:	07/12/21		
2	Air-cooled X Water-cooled								Ту	pe:		Screw
	Lubricated X Oil-Free				# of Stages:			ges:	2			
3*	Full Load Operating Pressure ^b						100					psig ^b
4	Drive Motor I	Nominal	Rating				75		hp			
5	Drive Motor Nominal Efficiency						95.2		percent			
6	Fan Motor Nominal Rating (if applicable)				le)		0.5		hp			
7	Fan Motor Nominal Efficiency						70.0		percent			percent
	Input Power (kW)					Capac	city (acf	m) ^{a,d}	Specific Power (kW/100 acfm) ^d			
	67.2						331		20.30			
	62.6					304			20	20.55		
8*	57.6					278		20	20.70			
	52.7					252		20.92				
	47.7					225			21.14			
	43.0						199		21.61			
9*	Total Package Input Power at Zero Flow ^{c, d}				w ^{c, d}		0.0					kW
		35.00										
		30.00										
	Power ACFM)	25.00										
10	Specific Power (kW/100 A.CFM)	20.00				_			-			
		15.00										
		10.00	50	100	150	200	250	300	350	400	450	500
		U	50	100		200 apacity (AC		500	550	400	4.30	500
	Note: Graph is only a sixual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 58W100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity											



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
 b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
 c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Ν	/le	m	be	

		ume Flow Rate ecified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power	
	m ³ /min	<u>ft³ / min</u>	%	%	%	
	Below 0.5	Below 17.6	+/- 7	+/- 8		
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
	1.5 to 15	53 to 529.7	+/- 5	+/- 6		
031.2	Above 15	Above 529.7	+/- 4	+/- 5		

ROT 02 12/19 R3