## **COMPRESSOR DATA SHEET**



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Gardner Denv	er					
	Model Number: Ultima U90-14	5psi	Date:	05/11/21			
2	Air-cooled X Water-co	poled	Type:				
	Lubricated X Oil Free		# of Stages:				
3*	Full Load Operating Pressure b	125	psig <sup>b</sup>				
4	Drive Motor Nominal Rating	60	<b>60</b> hp				
5	Drive Motor Nominal Efficiency	97.0	97.0 percent				
6	Fan Motor Nominal Rating (if applications)	able) <b>0.78</b>	<b>0.78</b> hp				
7	Fan Motor Nominal Efficiency	87.9	percent				
8*	Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>				
	100.44	505.9	19.85				
	91.85	454.2	20.22				
	83.52	402.5	20.75				
	75.47	350.9	21.51				
	67.71	299.2	22.63				
	60.19	247.5	24.32				
9*	Total Package Input Power at Zero Fl	ow <sup>c, d</sup> <b>8.0</b>	kW				
10	35.00  30.00  25.00  10.00  20.00  10.00  20.00  Capacity (ACFM)  Note: Graph is only a visual representation of the data in Section 8  Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35  X-Axis Scale, 10 to 25% over maximum capacity						

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{\mathbf{m}}^3 / \underline{\mathbf{min}}$	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	.,,,
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: U75-160B