COMPRESSOR DATA SHEET

Gardner Denver

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Gardner Denver						
	Model Number: L15-20hp-125psi	Date:	1/4/2021				
2	X Air-cooled Water-cooled	Type:	Screw				
		# of Stages:	1				
3*	Rated Capacity at Full Load Operating Pressure ^{a, e}	85.1	acfm ^{a,e}				
4*	Full Load Operating Pressure ^b	125	psig ^b				
5	Maximum Full Flow Operating Pressure ^c	130	psig ^c				
6	Drive Motor Nominal Rating	20	hp				
7	Drive Motor Nominal Efficiency	91	percent				
8	Fan Motor Nominal Rating (if applicable)	N/A	hp				
9	Fan Motor Nominal Efficiency	N/A	percent				
10*	Total Package Input Power at Zero Flow ^e	5.6	kW ^e				
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	17.95	kW^d				
12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e	21.09	kW/100 cfm ^e				
13	Isentropic Efficiency	71.21	Percent				

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator.

Consult CAGI website for a list of participants in the third party verification program: <u>www.cagi.org</u>

- NOTES:
- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the
- maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



	Volume Flow Rate at specified conditions		Volume Flow Rate	Consumption	No Load / Zero Flow Power
Member	$\underline{m}^3 / \underline{min}$	<u>ft³ / min</u>	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
ROT 030.1	Above 15	Above 529.7	+/- 4	+/- 5	
12/19 Rev 3 This form was develop	bed by the Compressed Air and C	as Institute for the use of its members participating	in the PVP. CAGI has not indeper	idently verified the reported da	a.

Configurator: L15-22C