COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Gardner Denver						
	Model Number: Ultima U160-145psi		Date:	05/11/21			
2	Air-cooled X Water-cooled		Type: Screw				
	Lubricated X Oil Free	:	# of Stages:	2			
3*	Full Load Operating Pressure b	145	psig				
4	Drive Motor Nominal Rating	107 hp					
5	Drive Motor Nominal Efficiency	97.0 percent					
6	Fan Motor Nominal Rating (if applicable)	0.78	hp				
7	Fan Motor Nominal Efficiency	87.9	percent				
	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d				
	174.86	835.0	20.94				
OΨ	150.81	722.3	20.88	}			
8*	128.61	609.7	21.09				
	107.96	497.1	21.72	,			
	88.84	384.5	23.11				
	71.17	271.9	26.18				
9*	Total Package Input Power at Zero Flow c, d	8.0		kW			
10	Note: Graph is only a v Note: Y-Axis Scale, 10 to 35,	Capacity (ACFM) isual representation of the data in Se , + 5kW/100acfm increments if necessa , 0 to 25% over maximum capacity	ction 8	900.0			

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{m}^3 / \underline{min}$	<u>ft³ / min</u>	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	.,,,
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: U75-160B