## **COMPRESSOR DATA SHEET**



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

1	Manufacturer: Gardner	· Denver				
		J <b>90-145psi</b>		Date:	05/11/21	
2	Air-cooled X Water-cooled			Type:	Screw	
	Lubricated X Oil Free			# of Stages:	2	
3*	Full Load Operating Pressure b		145 psig <sup>b</sup>			
4	Drive Motor Nominal Rating		60		hp	
5	Drive Motor Nominal Efficiency		97.0		percent	
6	Fan Motor Nominal Rating (if	f applicable) 0.78			hp	
7	Fan Motor Nominal Efficiency	7	87.9		percent	
	Input Power (kW)		Capacity (acfi	a.d I	Specific Power (kW/100 acfm) <sup>d</sup>	
	99.69		449.4		22.18	
Ovk	93.69		413.9	2	22.64	
8*	87.84		378.4	2	23.22	
	82.14		342.9		23.95	
	76.59		307.4	2	24.92	
	71.18		271.9		26.18	
9*	Total Package Input Power at Zero Flow c, d		8.0		kW	
10	35.00 30.00 Specific Power (kW/100 ACFM) 25.00 20.00					
	15.00		200.0 250.0  Capacity (ACFM)  risual representation of the	300.0 350.0 400.0  e data in Section 8 as if necessary above 35	450.0 500.0	

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power	
$\underline{\mathbf{m}}^3 / \underline{\mathbf{min}}$	ft <sup>3</sup> / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: U75-160B