47728696001 rev A



## **COMPRESSOR DATA SHEET**

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

	MODEL DATA - FO	R COMPRESSED	AIR		
1	Manufacturer: Gardner Denver				
	Model Number TVS74		Date:	07/12/21	
2	X Air-cooled Water-cooled		Type:	Screw	
	Lubricated X Oil-Free		# of Stages:	2	
3*	Full Load Operating Pressure <sup>b</sup>	125	psig <sup>b</sup>		
4	Drive Motor Nominal Rating	100	hp		
5	Drive Motor Nominal Efficiency	95.2	percent		
6	Fan Motor Nominal Rating (if applicable)	5.4	hp		
7	Fan Motor Nominal Efficiency	88.6	percent		
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>		
	92.4	400	23.10		
	81.9	351	23.37		
8*	72.9	310	23.53		
	64.2	269	23.86		
	55.5	229	24.28		
	49.1	198	24.80		
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	0.0	kW		
10	35.00 30.00 30.00 25.00 15.00 10.00 15.00 Note: Graph is only a visa	200 250 300  Capacity (ACFM)  all representation of the data in S.  5kW/100acfm increments if necess		450 500	

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
  b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
  d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m³/min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2 12/19 R3