## **COMPRESSOR DATA SHEET**



## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor: Variable Frequency Drive** 

		MOI	DEL DATA - 1	FOR COMPRESSI	ED AIR		
1	Manufacturer:	Gard	ner Denver				
	Model Number: L250RS-340hp-190psi  X Air-cooled Water-cooled			i	Date:	01/04/2	
2					Type:	Screw	
					# of Stages:	1	
3*	Full Load Operating Pressure b			190		psig b	
4	Drive Motor Nominal Rating			340		hp	
5	Drive Motor Nominal Efficiency			95.0		percen	
6	Fan Motor Nominal Rating (if applicable)		3.0 / 7.4		hp		
7	Fan Motor Nom	inal Efficie	ncy	86.7 / 89.6		percen	
	Input Power (kW)			Capacity (acfm) <sup>a,d</sup>		Specific Power kW/100 acfm) <sup>d</sup>	
	272.03			1091.6		24.92	
Οψ	227.45			914.0		24.89	
8*	185.56			736.2		25.21	
	146.16			558.1		26.19	
	109.11			379.4		28.76	
	74.20			199.7		37.15	
9*	Total Package Input Power at Zero Flow c, d			22.2		kW	
10	Isentropic Efficiency			72.74		%	
11	Specific Power (kW/100 ACFM)	40.00 35.00 30.00 25.00 20.00 15.00 10.00 0.0	200.0	400.0 600.0	800.0 100	0.0 1200.0	
		1	Note: Y-Axis Scale, 10 to 3	Capacity (ACFM)  a visual representation of the data 35, + 5kW/100acfm increments if nealle, 0 to 25% over maximum capacit	cessary above 35		

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="https://www.cagi.org">www.cagi.org</a>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	olume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
$\underline{m}^3 / \underline{min}$	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: LRS160-290C