47728681001 rev A



COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR								
1	Manufacturer: Gardner Denver							
	Model Number TVS37		Date:	03/03/21				
2	X Air-cooled Water-cooled		Type:	Screw				
	Lubricated X Oil-Free		# of Stages:	2				
3*	Full Load Operating Pressure ^b	100	$psig^b$					
4	Drive Motor Nominal Rating	50	hp					
5	Drive Motor Nominal Efficiency	94.7	percent					
6	Fan Motor Nominal Rating (if applicable)	5.4	hp					
7	Fan Motor Nominal Efficiency	88.6	percent					
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) ^d					
	46.8	200	23.41					
	41.6	179	23.31					
8*	36.6	157	23.27					
	31.8	136	23.45					
	27.4	114	23.98					
	22.9	93	24.78					
9*	Total Package Input Power at Zero Flow ^{c, d}	0.0	kW					
	35.00							
	25.00 (William 20.00) 25.00							
10	15.00							
	10.00 0 25 50 75	100 125 150 175	200 225	250 275				
	Capacity (ACFM)							
	Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity							

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2

2/19 R3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data