47728695001 rev A



## **COMPRESSOR DATA SHEET**

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR								
1	Manufacturer: Gardner Denver							
2	Model Number TVS74	TVS74		07/12/21				
	X Air-cooled Water-cooled		Type:	Screw				
	Lubricated X Oil-Free		# of Stages:	2				
3*	Full Load Operating Pressure <sup>b</sup>	100	100 psig <sup>b</sup>					
4	Drive Motor Nominal Rating	100	hp					
5	Drive Motor Nominal Efficiency 95.2		percent					
6	Fan Motor Nominal Rating (if applicable)	5.4	hp					
7	Fan Motor Nominal Efficiency	88.6	percent					
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>					
	92.4	435	21.24					
O.t.	81.9	388	21.11					
8*	71.5	341	20.97					
	61.5	294	20.94					
	52.2	246	21.18					
	43.6	199	21.89					
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	otal Package Input Power at Zero Flow <sup>c, d</sup> 0.0 k		kW				
	35.00							
	30.00							
	Specific Power (KW/100 ACF/N) 20:00							
10	20.00							
	15.00							
	10.00 0 50 100 150	200 250 300	350 400	450 500				
	Capacity (ACFM)							
	Note: Y-Axis Scale, 10 to 3:	visual representation of the data in S 5, + 5kW/100acfm increments if necess e, 0 to 25% over maximum capacity						

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
  b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
  d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> /min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2 12/19 R3