

GMRC SERIES AIR COOLED CYCLING DRYER SPECIFICATIONS

MODEL	CAPACITY	NUMBER OF MODULES	AVAILABLE VOLTAGES	REFRIGERATION SYSTEM				TOTAL SYSTEM KW/H	PSID	IN/OUT HEADER	DIMENSIONS INCHES			WEIGHT (LBS)
				COMPRESSOR		CONDENSER					HEIGHT	WIDTH	DEPTH	
				HP	KW/H	CFM	KW/H							
GMRC2700	2700	2	208-230/3/60 460/3/60 575/3/60	9	18.20	22800	3.036	22.73	2.0	6" Flg	126	101	98	10090
GMRC3700	3700	2		10	23.78	22800	3.036	28.32	2.5	8" Flg	126	101	98	10450
GMRC4000	4000	2		12	27.20	22800	3.036	31.74	3.0	8" Flg	126	101	98	10620
GMRC4500	4500	2		13.5	31.33	22800	3.036	35.87	3.4	8" Flg	126	101	98	10750
GMRC5400	5400	3		10	35.68	34200	4.554	42.48	2.5	8" Flg	126	151	98	15510
GMRC6000	6000	3		12	40.80	34200	4.554	47.6	3.0	8" Flg	126	151	98	15675
GMRC6700	6700	3		13.5	47.00	34200	4.554	53.81	3.3	10" Flg	126	151	98	15975
GMRC7200	7200	4		10	47.57	45600	6.072	56.64	2.5	10" Flg	126	202	98	20970
GMRC8000	8000	4		12	54.40	45600	6.072	63.47	3.0	12" Flg	126	202	98	21270
GMRC8900	8900	4		13.5	62.67	45600	6.072	71.74	3.3	12" Flg	126	202	98	21400
GMRC10000	10000	5		12	68.00	57000	7.590	79.34	3.0	14" Flg	126	252	98	25995
GMRC11250	11250	5		13.5	78.34	57000	7.590	89.68	3.4	14" Flg	126	252	98	26165

GMRC SERIES WATER COOLED CYCLING DRYER SPECIFICATIONS

MODEL	CAPACITY	NUMBER OF MODULES	AVAILABLE VOLTAGES	REFRIGERATION SYSTEM				TOTAL SYSTEM KW/H	PSID	IN/OUT HEADER	DIMENSIONS INCHES			WEIGHT (LBS)
				COMPRESSOR		CONDENSER					HEIGHT	WIDTH	DEPTH	
				HP	KW/H	GPM	CONN.							
GMRC3200	3200	2	208-230/3/60 460/3/60 575/3/60	9	16.91	26.13	2" NPT	18.41	2.3	6" Flg	101	101	98	9340
GMRC4000	4000	2		10	21.88	29.27	2" NPT	23.38	2.7	8" Flg	102	101	98	9700
GMRC4800	4800	2		12	25.29	31.66	2" NPT	26.79	3.6	8" Flg	102	101	98	9870
GMRC5200	5200	2		13.5	29.09	34.67	2" NPT	30.59	3.9	8" Flg	102	101	98	10000
GMRC6100	6100	3		10	32.83	44.68	2" NPT	35.08	2.8	8" Flg	102	151	98	14540
GMRC7200	7200	3		12	37.93	47.5	2" NPT	40.18	3.6	8" Flg	102	151	98	14700
GMRC7800	7800	3		13.5	43.64	52.01	2" NPT	45.89	3.9	10" Flg	104	151	98	15000
GMRC8100	8100	4		10	43.77	59.58	2" NPT	46.77	2.8	10" Flg	104	202	98	19670
GMRC9600	9600	4		12	50.72	63.33	2" NPT	53.57	3.6	12" Flg	105	202	98	19970
GMRC10400	10400	4		13.5	58.18	69.35	2" NPT	61.18	3.9	12" Flg	105	202	98	20100
GMRC12000	12000	5		12	63.21	79.16	2" NPT	66.97	3.6	14" Flg	106	252	98	24370
GMRC13000	13000	5		13.5	72.72	86.69	2" NPT	76.48	3.9	14" Flg	106	252	98	24540

Capacity reflects SCFM at 100 PSIG, 100° F inlet conditions & 100° F ambient.

Inlet/outlet connections are 150# ANSI RF flanges.

Watts specified assume 35° F evaporator and 100° F ambient at full load conditions.

Dimensions are in inches. Dimensions and specifications are subject to change without notice.

Condenser flow requirements on water cooled models are based on 85° F water.