COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR Manufacturer: 1 **Gardner Denver ENV T200-125psi** 5/11/2021 Model Number: Date: 2 \mathbf{X} Water-cooled Air-cooled Screw Type: Oil-free 2 Oil-injected # of Stages: Rated Capacity at Full Load Operating Pressure a, e acfm^{a,e} 3* 1236.0 Full Load Operating Pressure b 125 4 psig Maximum Full Flow Operating Pressure c psig^c 5 125 **Drive Motor Nominal Rating 268** 6 hp **Drive Motor Nominal Efficiency** 7 **95.8** percent Fan Motor Nominal Rating (if applicable) 8 4X 3.7 hp Fan Motor Nominal Efficiency 9 86.5 percent Total Package Input Power at Zero Flow^e kW^{e} 10* **56.3** Total Package Input Power at Rated Capacity and 11 kW^{d} 246.90 Full Load Operating Pressure^d Specific Package Input Power at Rated Capacity 12* 19.98 $kW/100 cfm^e$ and Full Load Operating Pressure

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

| NOTE. The terms power and energy are synonymous for purposes of this document. | | | | | |
|--|--|-----------------------------|------------------|--------------------------------|------------------------------|
| | Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
| | m ³ /min | <u>ft³ / min</u> | % | % | % |
| | Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | +/- 10% |
| | 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | |
| | 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | |
| | Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

Member

ROT 030.2

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: ENVT165-315A