## **COMPRESSOR DATA SHEET**



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

| MODEL DATA - FOR COMPRESSED AIR |   |   |   |          |  |  |  |
|---------------------------------|---|---|---|----------|--|--|--|
| 1                               | Manufacturer: Gardner Denver  |   |   |          |  |  |  |
| 2                               | Model Number: ENV TVS200 -145psi  |   | Date:                                     | 05/11/21 |  |  |  |
|                                 | Air-cooled X Water-cooled   |   | Type:                                     | Screw    |  |  |  |
|                                 | Lubricated X Oil Free   |   | # of Stages:                              | 2        |  |  |  |
| 3*                              | Full Load Operating Pressure b  | 145   | psig b                                    |          |  |  |  |
| 4                               | Drive Motor Nominal Rating  | <b>268</b> hp   |   | hp       |  |  |  |
| 5                               | Drive Motor Nominal Efficiency  | 96.1 percent  |   | percent  |  |  |  |
| 6                               | Fan Motor Nominal Rating (if applicable)  | 2   | hp  |          |  |  |  |
| 7                               | Fan Motor Nominal Efficiency  | 86.5  | percent                                   |          |  |  |  |
|                                 | Input Power (kW)  | Capacity (acfm) <sup>a,d</sup>  | Specific Power (kW/100 acfm) <sup>d</sup> |          |  |  |  |
|                                 | 237.70  | 1087.7  | 21.85                                     |          |  |  |  |
| 8*                              | 221.60  | 1010.0  | 21.94                                     |          |  |  |  |
| 8*                              | 204.60  | 921.7   | 22.20                                     |          |  |  |  |
|                                 | 187.50  | 826.4   | 22  | .69      |  |  |  |
|                                 | 170.50  | 731.0   | 23  | .32      |  |  |  |
|                                 | 154.10  | 635.7   | 24.24                                     |          |  |  |  |
| 9*                              | Total Package Input Power at Zero Flow c, d   | 26.8  |   | kW       |  |  |  |
| 10                              | 35.00 30.00 25.00 25.00 15.00 10.00 200.0 400   |   | 00.0 1000.0                               | 1200.0   |  |  |  |
|                                 | Capacity (ACFM)  Note: Graph is only a visual representation of the data in Section 8 |   |   |          |  |  |  |
|                                 | Note: Y-Axis Scale, 10 to 35,   | the data in Solution of the data in Solution 5 the data in Solution | ary above 35                              |          |  |  |  |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

| Volume Flow Rate at specified conditions              |                       | Volume Flow Rate | Specific Energy<br>Consumption | No Load / Zero<br>Flow Power |
|---|-----------------------|------------------|--------------------------------|------------------------------|
| $\underline{\mathbf{m}}^3 / \underline{\mathbf{min}}$ | ft <sup>3</sup> / min | %                | %                              | %                            |
| Below 0.5   | Below 17.6            | +/- 7            | +/- 8                          |                              |
| 0.5 to 1.5  | 17.6 to 53            | +/- 6            | +/- 7                          | +/- 10%                      |
| 1.5 to 15   | 53 to 529.7           | +/- 5            | +/- 6                          |                              |
| Above 15  | Above 529.7           | +/- 4            | +/- 5                          |                              |

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: ENVTVS200-315A