COMPRESSOR DATA SHEET



In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Displacement

MODEL DATA - FOR COMPRESSED AIR												
1	Manufacturer:	Gard	ner Der	iver								
	Model Number:	25psi]	Date:		01/04/21				
2	X Air-cooled Water-cooled							7	Гуре:		Screw	
	X Lubricated Oil Free							# of St	ages:		1	
3*	Full Load Opera	ull Load Operating Pressure b					25		psig b			
4	Drive Motor No	Drive Motor Nominal Rating					00		hp			
5	Drive Motor Nominal Efficiency					9:	5.8		percent			
6	Fan Motor Nominal Rating (if applicable)					1	10		hp			
7	Fan Motor Nom	Fan Motor Nominal Efficiency					8.5		percent			
	Input Power (kW)					Capacity (acfm) ^{a,d}				Specific Power (kW/100 acfm) ^d		
	168.0					8	02		4			
8*	156.6				7	22		2				
	135.6				5	61		2	24.17			
	118.1					4	01			29.45		
	112.9			1	321 35.17			35.17				
9*	Total Package Input Power at Zero Flow c, d				, u	32	2.1		kW			
10	Isentropic Efficiency at Full Flow Rated Capacity and Full Load Operating Pressure					7	1.7		%			
		40.00										
		35.00										
	FM)	30.00	0									
	fic Pov	25.00										
11	Specific Power (kW/100 ACFM)											
		20.00	,									
		15.00	5.00									
		10.00	T		T	ı	Т	ı	-	ı		
		0	100	200	300	400	500	600	700	800	900	
					nly a visua	Capacity (ACFM) sual representation of the data in Section 8						
	Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity											

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

1	olume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{m}^3 / \underline{min}$	<u>ft³ / min</u>	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	.,
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 032.1

6/20. Rev2 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

Configurator: EAU99AA